## **905**63

WIDTH: 300 cm

WEIGHT: 900 g/sqm

JUMBO ROLLS\*: ± 300 lm

LENGTHS\*: ± 30 Im





S

Ш  $\Box$  $\triangleleft$ 

> Z

 $\triangleleft$ 

ш

ш

 $\triangleleft$ ⋖

## **ADVANTAGES**

- ► ROLL-WIDTH 300 CM, OPTIMUM FOR SIDE CURTAINS
- PANAMA BASE CLOTH: CONSIDERABLE MECHANICAL STRENGTH
- ANTI-THEFT OPTION WITH DEFENDER® (P. 44)

## **COLOURS & REFERENCES**

(COLOURS ARE INDICATIVE)

Ref. 905F3-31066	RAL 9016*
Ref. 905F3-31076	RAL 1015*
Ref. 905F3-31061	RAL 1003*
Ref. 905F3-31063	RAL 2004*
Ref. 905F3-31064	-
Ref. 905F3-31065	RAL 3002*
Ref. 905F3-31050	RAL 5013*
Ref. 905F3-31058	-
Ref. 905F3-31051	RAL 5002*
Ref. 905F3-31052	RAL 5010*
Ref. 905F3-31053	RAL 5015*
Ref. 905F3-31055	RAL 6026*
Ref. 905F3-31069	RAL 7035*
Ref. 905F3-31080	-
Ref. 905F3-31071	RAL 7038*
Ref. 905F3-31072	RAL 7040*
Ref. 905F3-31070	RAL 7037*
Ref. 905F3-31075	RAL 9005*

\*RAL reference

## TECHNICAL SPECIFICATIONS

	905F3	Standards
Yarn	2 x 1100 dtex PES H	Г
WEIGHT	900 g/sqm	EN ISO 2286-2
WIDTH	300 cm	
TENSILE STRENGTH (WARP/WEFT)	400/380 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	45/45 daN	DIN 53.363
FLAME RETARDANCY	55 mm/min	ISO 3795
Adhesion	10/10 daN/5 cm	EN ISO 2411
FINISH	VARNISH BOTH SIDES	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	