

## LIGHT

WIDTH: 204 cm(1)

WEIGHT: 280 g/sqm

LENGTHS\*: ± 50 lm



STAMOID®  $_{\Omega}$  $\triangleleft$ 

S

ш

 $\geq$ 

 $\triangleleft$ 

 $\alpha$  $\triangleleft$ 

 $\supset$ J







## **ADVANTAGES**

- EXTREMELY LIGHT AND EXCEPTIONALLY FLEXIBLE
- **MINIMUM SPACE REQUIREMENT**
- **■ OPTIMUM UV RESISTANCE**
- HIGH TEAR STRENGTH
- **■> 100** % WATERPROOF (INCLUDING SEA-WATER)
- **DIRT RESISTANT**; **ANTI-CAPILLARITY TREATMENT NANOTOP®**
- Accessories: Stamoid® Edge (p. 79) FERRARI® SILCORD (P.80)
- **MAINTENANCE: FERRARI® CLEAN (P. 81)**

## **COLOURS & REFERENCES**

(COLOURS ARE INDICATIVE)

Ref. 4128-03244

Ref. 4128-10001

Ref. 4128-01897

Ref. 4128-04348

Ref. 4128-10235

## TECHNICAL SPECIFICATIONS

	Ferrari® Stamoid 4128 light	Standards
YARN	280 dtex PES HT	TERSUISSE
WEIGHT	280 g/sqm	EN ISO 2286-2
WIDTH	204 cm (ref. 10124 : 150 cm)	
TENSILE STRENGTH (WARP/WEFT)	100/100 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	7/7 daN	DIN 53.363
FINISH & MAKING-UP	One-side coating - Varnish on face / Fabric make-up by sewing only	
HANDLING TEMPERATURE RANGE	-20°C/+70°C	
QUALITY MANAGEMENT SYSTEM		ISO 9001

Ref. 4128-10124 (1)Only in 150 cm roll-widths

The technical characteristics shown are average values given as a guide and may be modified. \*Our packaging data are given for information only and may vary as a function of manufacturing conditions.