

PRECONTRAIT® 501

WIDTH: 180 cm	WEIGHT: 530 g/sqm
JUMBO ROLLS*: ± 350 lm	LENGTHS*: ± 50 lm

WIDTH: 270 cm (white)	WEIGHT: 530 g/sqm
JUMBO ROLLS*: ± 350 lm	LENGTHS*: ± 30 lm



INDUSTRIAL SUSPENDED CEILING

INDUSTRIAL DIVIDING WALLS

GUARANTEES AND LABELS



ADVANTAGES

- **FERRARI® PRÉCONTRAIT® TECHNOLOGY:**
 - EXCEPTIONAL DIMENSIONAL STABILITY
 - HIGH DURABILITY
 - EXCELLENT WELDABILITY
- **ANTI DIRT MATT VARNISH**
- **HIGH-PERFORMANCE (M1/B1) FLAME RETARDANCY FOR INTERIOR APPLICATIONS**
- **EUROCLASS: B-s1,d0, WITH A 40 MM MINIMUM THICK AIR GAP IN ACCORDANCE WITH EN 1305-1 STANDARD.**
- **ACCESSORY: FERRARI® SILCORD (P. 80)**

COLOURS & REFERENCES (COLOURS ARE INDICATIVE)

	Ref. 501-790 (Only in 270 cm roll-widths)
	Ref. 501-8861
	Ref. 501-8390
	Ref. 501-8450

TECHNICAL SPECIFICATIONS

	PRÉCONTRAIT® 501	STANDARDS
YARN	1100 dtex	TERSUISSE
WEIGHT	530 g/sqm	EN ISO 2286-2
WIDTH	180 cm (except white in 270 cm)	
TENSILE STRENGTH (WARP/WEFT)	200/250 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	20/16 daN	DIN 53.363
ADHESION	8/8 daN/5 cm	EN ISO 2411
FINISH	VARNISH BOTH SIDES	
FLAME RETARDANCY	M1/NFP 92-507 • B1/DIN 4102-1 • CLASSE 1/UNI 9177 • M1/UNE 23.727 • TEST 1 & TEST 2/NFPA 701 •	
EUROCLASS	B-s1,d0/EN 13501-1	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM	ISO 9001	

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.