

STAMISOL®

371FT

WEIGHT: 440 g/sqm	POROSITY: ± 20 %
	LENGTHS*: ± 50 lm



ADVERTISING FACADE



TEXTILE CLADDING



GUARANTEES AND LABELS




ADVANTAGES

- REMARKABLE THERMAL AND ENERGY PERFORMANCE
- SOLAR AND LIGHT PROTECTION
- FOR IMPROVED VISUAL COMFORT
- FLEXIBLE AND LIGHT MEMBRANES FOR NEW CONSTRUCTION OR RENOVATION
- CUSTOMIZED GRAPHICS, AND/OR 3D EFFECT

COLOURS & REFERENCES

(COLOURS ARE INDICATIVE)



Ref. 371-790

Ref. 371-3048

TECHNICAL SPECIFICATIONS

	STAMISOL® 371FT				STANDARDS
YARN	1100/2200 dtex PES HT				TERSUISSE
WEIGHT	440 g/sqm				EN ISO 2286-2
WIDTH	267 cm				
TENSILE STRENGTH (WARP/WEFT)	300/300 daN/5 cm				EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	60/60 daN				DIN 53.363
ADHESION	9/9 daN/5 cm				EN ISO 2411
POROSITY	± 20%				
THERMAL VALUES (RÉF. 371-790) (RÉF. 371-3048)	TS 30%	RS 56%	AS 14%	FS 32%	ASHRAE STANDARD 74-1988 TS : SOLAR TRANSMISSION RS : SOLAR REFLECTION AS : SOLAR ABSORPTION
FLAME RETARDANCY	M1/NFP 92-507 • B1/DIN 4101-1 VKF 5.3/SN 198898				
EUROCLASS	B-s2,d0				
HANDLING TEMPERATURE RANGE	-30°C/+70°C				
QUALITY MANAGEMENT SYSTEM					ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.