

1250/1300

WIDTH: 260 cm

WEIGHT: 1250/1350 g/sqm

JUMBO ROLLS*: ± 300 lm / ON REQUEST⁽¹⁾



LAKE LINER



DAM



HOLDING TANK

GUARANTEES AND LABELS



(On request)



ADVANTAGES

- **GOOD RESISTANCE TO ACID AND BASE PRODUCTS**
- **COMPATIBLE WITH LIVE STOCK AND FISH FARMING**
- **POLYESTER HIGH TENACITY BASE CLOTH**
- **BALANCE BETWEEN WEIGHT AND STRENGTH**
- **HYDROPHOBIC COATING**
- **U.V. AND FUNGUS TREATED**
- **2 COLOUR REVERSABLE MEMBRANE**
- **RECOMMENDATION OF USE DEPENDS UPON APPLICATION: PLEASE CONTACT US**
- **⁽¹⁾ STAMOID® 1300 : MINIMUM ORDER OF 2500 LINEAR METRES REQUIRED**

COLOURS & REFERENCES

(COLOURS ARE INDICATIVE)



1 green side and 1 beige side

Ref. S1250-20046 TYP I RAL 1001-6033
ord. 13297

Ref. S1300-20046 TYP II RAL 1001-6033
ord. 13299

TECHNICAL SPECIFICATIONS

	STAMOID® 1250	STAMOID® 1300	STANDARDS
YARN	1100 dtex PES HT	2 x 1100 dtex PES HT	TERSUISSE
WEIGHT	1250 g/sqm	1350 g/sqm	EN ISO 2286-2
WIDTH	260 cm	260 cm	
COATING DOUBLE FACE	PVC	PVC	
THICKNESS	1 mm (+0,1/-0)	1 mm (+0,1/-0)	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5cm	400/400 daN/5cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	24/24 daN	50/50 daN	DIN 53.363
ADHESION	15/15 daN/5 cm	16/16 daN/5 cm	EN ISO 2411
HANDLING TEMPERATURE RANGE	-40°C/+70°C	-40°C/+70°C	
QUALITY MANAGEMENT SYSTEM			ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.