

STAMOID®

5000

UNO FR

WIDTH: 220 cm	WEIGHT: 680 g/sqm
	LENGTHS*: ± 50 lm

WIDTH: 260 cm	WEIGHT: 680 g/sqm
JUMBO ROLLS*: ± 300 lm	LENGTHS*: ± 50 lm



LIGHT STRUCTURES



STANDS



TEMPORARY LABORATORY

GUARANTEES AND LABELS



ADVANTAGES

- **EXCEPTIONAL FLEXIBILITY**
- **STAMTOP® ANTI-DIRT FINISH**
- 22 COLOURS AVAILABLE IN 260 CM
10 COLOURS AVAILABLE IN 220 CM
- FLAME RETARDENCY CONFORMS TO A NUMBER OF STANDARDS
- **ANTI-THEFT OPTION WITH DEFENDER® (P. 44)**

COLOURS & REFERENCES (COLOURS ARE INDICATIVE)

	Ref. 5000-20000 220 cm / 260 cm	RAL 9010
	Ref. 5000-20001 220 cm / 260 cm	RAL 7035
	Ref. 5000-20025 220 cm / 260 cm	RAL 7038
	Ref. 5000-20024*	RAL 7040
	Ref. 5000-20023 220 cm / 260 cm	RAL 7037
	Ref. 5000-20022*	RAL 7031
	Ref. 5000-20007 220 cm / 260 cm	RAL 9005
	Ref. 5000-20015*	RAL 1021
	Ref. 5000-20012*	RAL 1003
	Ref. 5000-20013 220 cm / 260 cm	RAL 2004
	Ref. 5000-20011*	RAL 3002
	Ref. 5000-20016*	RAL 5002
	Ref. 5000-20009 220 cm / 260 cm	RAL 5012
	Ref. 5000-20017*	RAL 5012
	Ref. 5000-20018*	RAL 6026
	Ref. 5000-20003 220 cm / 260 cm	RAL 6029
	Ref. 5000-20010*	RAL 6029
	Ref. 5000-20021*	RAL 6018
	Ref. 5000-20005 220 cm / 260 cm	RAL 1014
	Ref. 5000-20020*	RAL 1014
	Ref. 5000-20002 220 cm / 260 cm	RAL 8017
	Ref. 5000-20004*	RAL 8017

*Only in 260 cm roll-widths

TECHNICAL SPECIFICATIONS

	STAMOID® 5000 UNO FR	STANDARDS
YARN	1100 dtex PES HT	TERSUISSE
WEIGHT	680 g/sqm	EN ISO 2286-2
WIDTH	220 cm 260 cm	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	28/28 daN	DIN 53.363
ADHESION	10/10 daN/5 cm	EN ISO 2411
FINISH	STAMTOP® VARNISH BOTH SIDES	
FLAME RETARDANCY	M2/NFP 92.507 • B1/DIN 4102-1 • FAR/JAR/CS 25.853 VKF-5.2/SN 198898 • BS 7837 - SIS 650082	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM		ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.