

STAMOID®

5005 S

OPAQUE

WIDTH: 260 cm	WEIGHT: 680 g/sqm
JUMBO ROLLS*: ± 350 lm	LENGTHS*: ± 50 lm



STORAGE HALL



EVENT STRUCTURES



GUARANTEES AND LABELS



ADVANTAGES

- HIGH TENACITY
- EXCELLENT WELDABILITY
- **EXCEPTIONAL FLEXIBILITY**
- **RESISTANT AND ADAPTABLE TO LONG-TERM APPLICATIONS**
- **HIGH DEGREE TO UV AND BAD WEATHER RESISTANCE**
- STAMTOP® S FLUORINATED VARNISH:
 - EXCELLENT DIRT RESISTANCE AND CLEANABILITY
- **POSSIBILITY TO PRODUCE OTHER COLOURS ON THE FACE/REVERSE SIDE ON REQUEST**
- **ACCESSORIES: PRÉCONTRAIT® 709 (P. 77)**
FERRARI® KEDER (P. 78)
- **EASY MAINTENANCE: FORMULA S (P. 81)**

COLOURS & REFERENCES

(COLOURS ARE INDICATIVE)



White face

Black back side

Réf. 5005-20103 opaque

TECHNICAL SPECIFICATIONS

	STAMOID® 5005 S OPAQUE	STANDARDS
YARN	1100 dtex PES HT	TERSUISSE
WEIGHT	680 g/sqm	EN ISO 2286-2
WIDTH	260 cm	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	30/30 daN	DIN 53.363
ADHESION	10/10 daN/5 cm	SN EN ISO 2411
FINISH	STAMTOP® S VARNISH	
FLAME RETARDANCY (260 CM)	VKF 5.2/SN 198 888 • M2/NFP 92-507 • B1/DIN 4102-1 • CSFM 19 • NFPA 701	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM		ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.